## Flow Rates of Filter Bags

In most filtration applications, fluid viscosities do not exceed 50cps. Using the following Flow Rates Per #2 Size Bag as a guide, the suggested flow rates should result in a CLEAN Pressure Drop under 2 PSID.

Micron Rating	Flow Rate (GPM)
1 & 3	80 GPM/#2 BAG
5 THRU 200	120 GPM/#2 BAG
1,5 & 10	100 GPM/#2 BAG
25 THRU 100	125 GPM/#2 BAG
150 THRU 800	150 GPM/#2 BAG
1A and 2A	60 GPM/#2 BAG
10A, 25A, 90A & 0A	80 GPM/#2 BAG
	1 & 3 5 THRU 200 1,5 & 10 25 THRU 100 150 THRU 800

## Micron Rating & Availability

Micron Availability			Micron Rating																						
Fiber	Material	1	3	5	10	25	35	50	65	75	90	100	120	125	150	175	200	250	300	400	009	700	800	1200	1500
Polyester Felt	Felt																								
Nylon	Felt																								
Polypropylene	Felt																								
Teflon®	Felt																								
High Temperature	Felt																								
Polypropylene	Microfiber																								
Nylon	Monofilament Mesh																								
Polypropylene	Monofilament Mesh																								
Polyester	Multifilament Mesh																								