

DECLARATION OF COMPLIANCEPall® Oenofine XL Filter Modules

"W" Code

Module Part Numbers:

WUSP-6443

The Oenofine XL filter modules are designed for contact with non-fatty foodstuffs. These modules can be used with aqueous and alcoholic foodstuffs (up to 65 % alcohol) at up to 40 °C (104 °F) in filtration flow conditions, following flushing and in flow conditions.

An initial flush is mandatory prior to use.

Issued 1 May 2010
Revison 18 May 2016
Expires 28 February 2017
Reference FBDCOFINEENi

Page 1 of 3

Lorenz Strenge Quality Manager Pall Filtersystems GmbH

Oenofine XL Filter Modules (W Code)

Components

Membrane PVDF

Housing Polysulfone

Potting and Cross-plate Epoxy Resin

Netting Polyethylene

Sleeve Polypropylene

O-ring Seal Ethylene Propylene Copolymer

Note: may contain trace levels of Bisphenol A

The modules are packaged with the following solution:

Glycerin 65 %, Ethanol 2 % and Water 33 %

The modules must be flushed prior to use to remove this solution.

Declaration

Oenofine XL filter WUSP-6443 modules comprise of materials that meet regulatory and legislative requirements and guidelines for food contact in that:

Europe

The "W" Code Oenofine XL module, WUSP-6443, meets the requirements for food contact as detailed in European Regulation (EC) Numbers 1935/2004 in that:

- The products have been assessed by the manufacturer, in conjunction with a Consulting and Testing Service, under the
 Plastics Materials and Articles in Contact with Foodstuffs Regulations laid out in EU Regulation (EU) number 10/2011. All
 substances identified as being used in the manufacture of the above products were (a) listed in the above legislation either
 with or without restrictions, or (b) not subject to the provisions of the above legislation.
- The supplier certifies that the materials of construction are not subject to the provisions of EC Regulation 1895(2005) and/or
 do not use BADGE, BFDGE or NOGE.
- Tests have shown that the WUSP-6443 module will meet the Specific Migration Limits and the Overall Migration Limits in 3 % acetic acid and alcoholic liquids up to 65 % ethanol when tested under conditions of repeat usage at 40 °C (104 °F), provided that the flow rate through the filters is greater than the minimum recommended flow rate of 90 L per hour

USA

The manufacturer states that the following materials of construction are listed for food contact use as detailed in Code of Federal Regulations, 21 CFR paragraphs 170-186 in that:

- Polyethylene to 21 CFR section 177.1520 (Olefin polymers)
- PVDF to 21 CFR section 177.2510 (Polyvinylidene fluoride resins)
- Polysulfone to 21 CFR section 177.1655 (Polysulfone resins)
- Epoxy resin to 21 CFR section 175.300 (Resinous and polymeric coatings)
- Polypropylene to 21 CFR section 177.1520 (Olefin polymers)

Note: may contain trace levels of Bisphenol A - a chemical subject to State of California Prop-65 listing. BPA is known to cause reproductive toxicity.

Process Quality System

Country of Origin: Japan

This product is manufactured under a Quality Management System certified to ISO 9001:2008.

Contact in Europe

Pall Filtersystems GmbH Planiger Strasse 137 55543 Bad Kreuznach Germany

Supplied in Europe by

Pall International Sàrl Av. De Tivoli 1700 Fribourg Switzerland



Pall Food and Beverage

New York - USA +1 516 484 3600 telephone +1 866 905 7255 toll free foodandbeverage@pall.com

Visit us on the web at www.pall.com

Pall Corporation has offices throughout the world. For Pall representatives in your area, please go to www.pall.com/contact.

Because of developments related to products, systems and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid.

© Copyright 2016, Pall Corporation. Pall and (ALL) are trademarks of Pall Corporation. ® indicates a trademark registered in the USA. Filtration.Separation.Solution is a service mark of Pall Corporation.

FBDCOFINEENi May2016